

## DECT 312 Wireless PBX System

**This is a fully functional PBX system  
Not a multi handset cordless phone**



- \*For 1, 2 or 3 telephone lines
- \*No wiring required – plug and play within minutes!
- \*Supplied with 3 handsets
- \*Capacity for up to 12 handsets
- \*Auto Attendant On or Off– (ie: pre-recorded voice prompts for selecting an extension)
- \*Handset Speaker Phone
- \*Put calls on hold
- \*Call Transfer to other handsets
- \*Comfort tone whilst calls are on hold or being transferred.
- \*Intercom between handsets
- \*Back Lit LCD Display – Date & Time, extension number, call timer, battery level etc
- \*Caller ID Compatible
- \*Phone Line Auto Search -Will automatically search for the next available line or you can manually select.
- \*30 Phone book memories
- \*30 Caller ID memories
- \*30 Last number re-dial memories
- \*10 Different ringer melody options for external and internal calls
- \*4 level handset volume control
- \* 4 level handset ringer volume for all calls including option to switch off ringer.
- \*Off hook dialing and pre-dialing
- \*Multi Language (English, French, Spanish, Dutch, German, Italian, Portuguese & Chinese)
- \*Out of range tone – 40m internal & 150m external line of sight
- \*GAP Compliant – compatible with most other DECT handsets but limited functionality
- \* Key pad lock function
- \*Alarm function
- \*CE & RoHS Compliant

### Specifications

Frequency	1880-1895MHz
Frequency modulation	GFSK
Air interface	TDMA/TDD
Channel space	1.728MHz
Carrier frequency offset	<±50KHz
Output power	Max. 250mW Avg. 10mW
Charging time	12 hrs
Temperature	Normal:15°C~35°C Special:0°C~40°C
Humidity	0%~90%
Dimensions(mm)	Base:145x133x29 Handset:160x46x22
Power	Base input:DC9V 0.5A - HS charger:DC7V 0.42A HS Battery:Ni-MH 1.2Vx2,600mAh