

BELL BUTTON

WITH AUTOMATICALLY ILLUMINATED NAMEPLATE

2 FAMILIE
FAMILY
FAMILIE

KTD-2


- High-quality die-cast aluminium casing, colour coated available in silver or anthracite
- Economical LED lighting, power consumption approx. 1.5 W
- Light sensor-controlled doorbell button illumination automatically turns **ON** in the dark, and **OFF** at brightness
- Brightness of the bell button lighting adjustable in 3 steps
- Visual reassurance of bell button activation by short green light (can be switched off)
- 2 LED down light e.g. for illuminating a door sill (can be switched off)

Simple surface mounting

- Weathering resistant according to IP 44
- Dry output for connecting doorbell / gong
- Contact rating: max. 24V / 1A
- Temperature range: -20 to + 50° C
- Including fixing material (screws, dowels and drilling template)

LIGHT INTENSITY
DIMMABLESWITCHABLE
DOWNLIGHTS

ANWENDUNGSBEISPIELE

OPTICAL SIGNALLING
When the doorbell button is pressed
it briefly lights up green

KTD - 2

TECHNICAL DATA

MODEL	KTD-2 S (Art. no: 41049) silver	KTD-2 A (Art. no: 41051) anthracite
SCOPE OF DELIVERY	1x die-cast aluminium bell button, mounting material	
DEVICES	114 x 114 x 22mm (w x h x d)	
GIFTBOX	180 x 254 x 65 mm (w x h x d) • 0.59kg	
EXPORT BOX	10 pieces • 300 x 290 x 210 mm (w x h x d) • 6.3 kg	
POWER SUPPLY	8-24V AC/DC max. 1A • power consumption < 1.5W	
ADDITIONAL INFO	Surface mounting • Temperature range: -20°C to +50°C	
APPROVAL	CE • European Union	
EAN	Mod. KTD-2 S: 4250109135288	KTD-2 A: 4250109135301