

# BELL BUTTON


## WITH AUTOMATICALLY ILLUMINATED NAMEPLATE

**1** FAMILIE  
FAMILY  
FAMILIE

- Aluminium casing with brushed 3 mm stainless steel front plate
- Economical LED lighting, power consumption approx. 1.5 W
- Light sensor-controlled doorbell button illumination automatically turns "on" in the dark, and "OFF" at brightness
- Brightness of the bell button lighting adjustable in 3 steps
- Visual reassurance of bell button activation by short green light (can be switched off)
- 2 LED down light e.g. for illuminating a door sill (can be switched off)
- Simple surface mounting
- Weathering resistant according to IP 44
- Dry output for connecting doorbell / gong
- Contact rating: max. 24V / 1A
- Temperature range: -20 to + 50° C
- Including fixing material (screws, dowels and drilling template)

**LUMINOUS INTENSITY  
DIMMABLE**

**SWITCHABLE  
DOWN LIGHTS**

EXAMPLE OF USE
**VISUAL REASSURANCE**  
After pressing the bell button  
briefly lights up green

**KTE - 1**
**TECHNICAL DATA**

<b>MODEL</b>	KTE-1	Art. no: 41026
<b>SCOPE OF DELIVERY</b>	1x stainless steel bell button, mounting material	
<b>DEVICES</b>	114 x 114 x 22mm (w x h x d)	
<b>GIFTBOX</b>	160 x 254 x 65 mm (w x h x d) • 0.65kg	
<b>EXPORT BOX</b>	10 pieces	
<b>POWER SUPPLY</b>	8-24V AC/DC max. 1A • power consumption < 1.5W	
<b>ADDITIONAL INFO</b>	Surface mounting • Temperature range: -20°C to +50°C	
<b>APPROVAL</b>	CE • European Union	
<b>EAN</b>	4250109135257	