

BELL BUTTON

WITH AUTOMATICALLY ILLUMINATED NAMEPLATE

2 FAMILIE
FAMILY
FAMILIE

- Aluminium casing with brushed 3 mm stainless steel front plate
- Economical LED lighting, power consumption approx. 1.5 W
- Light sensor-controlled doorbell button illumination automatically turns "on" in the dark, and "OFF" at brightness
- Brightness of the bell button lighting adjustable in 3 steps
- Visual reassurance of bell button activation by short green light (can be switched off)
- 2 LED down light e.g. for illuminating a door sill (can be switched off)
- Simple surface mounting
- Weathering resistant according to IP 44
- Dry output for connecting doorbell / gong
- Contact rating: max. 24V / 1A
- Temperature range: -20 to + 50° C
- Including fixing material (screws, dowels and drilling template)


**LUMINOUS INTENSITY
DIMMABLE**

**SWITCHABLE
DOWN LIGHTS**

EXAMPLE OF USE
VISUAL REASSURANCE
After pressing the bell button
briefly lights up green

KTE - 2
TECHNICAL DATA

MODEL	KTE-2	Art. no: 41027
SCOPE OF DELIVERY	1x stainless steel bell button, mounting material	
DEVICES	114 x 114 x 22mm (w x h x d)	
GIFTBOX	180 x 254 x 65 mm (w x h x d) • 0.65kg	
EXPORT BOX	10 pieces	
POWER SUPPLY	8-24V AC/DC max. 1A • power consumption < 1.5W	
ADDITIONAL INFO	Surface mounting • Temperature range: -20°C to +50°C	
APPROVAL	CE • European Union	
EAN	4250109135264	