

Technical Parameters

Signalling protocol

SIP 2.0 (RFC - 3261)

Buttons

Quick dial buttons	Transparent, white backlit buttons with easily replaceable name tags
Number of buttons	1, 2 or 4
Numeric keypad	optional

Audio

Microphone	2 integrated microphones
Loudspeaker	1W (optionaly 10W)

Audio stream

Codecs	G.711, G.729
--------	--------------

Camera

Resolution	640 (Horizontal) x 480 (Vertical)
View angle	135° (H), 109° (V)
IR Night Vision	yes

Video stream

Codecs	H.263+, H.264, MPEG-4, M-JPEG
--------	-------------------------------

Interface

Power supply	12V±15%/1A DC or POE
PoE	PoE 802.3af (Class 0 - 12.95W)
LAN	10/100BASE-TX with Auto-MDIX
Relay outputs	NC/NO contacts, max 30V/1A AC/DC
Active relay output	12V/700mA DC

RFID card reader

Supported cards	EM-40XX (125Khz) HID Proximity (125kHz, 26 bit)
-----------------	--

Mechanical

Operating temperature range	-20°C – 55°C
Storage temperature range	-40°C – 70°C
Relative humidity	10% - 95% (not condensing)
Dimensions	217x109x83 mm
Protection level	IP 65, 69