

SECURACCESS COMPACT IP CAM



Audio and video IP doorphone

- Full hands free
- **Just 1 cable** to provide audio, video and power.
- **Monitor who is calling**, answer and activate the door latch from a SIP video phone or a PC (a free Pop-up video software is included)
- **Complying** with the main IP platforms (Alcatel, Astra, Avaya, SIP Centrex, Asterisk, etc.)

Door phone

- 1 or 2 dialling buttons
- **Flush** or surface mount
- Door latch activation NO/NC (2)
- **Backlighted** buttons
- Optional red colour

IP 65 Weatherproof protection

- Superior **resistance** to dust and water
- Perfect for outside installation

Vandal resistant

- **4 mm** thick aluminium housing
- Tamper resistant proof screws
- **Grid protection** for microphone and speaker

SIP

Powered over the Ethernet (PoE) or with an optional power supply

SIP v2 compatible (P2P or IPBX system)

DHCP client – Static @ IP

Web interface configuration

Security password



Features and specifications

Audio

- G.711, G.726, GSM Codecs.
- Microphone and speaker adjustments, echo cancellation
- Automatic or manual on-hook/off-hook settings choice
- Eeprom memory backup for stored codes and numbers
Up to 2 different numbers can be stored and activated according to 3 time slots choice per day (NTP server required) for each memory/call button.
- Alternative choice is the chain dialling (up to 2 stored numbers) for each button.

Compact IP	
PoE powered IEEE 802.3af/Optional power supply	✓/✓
Ethernet 10/100 Base T	1
SIP v2 (RFC 3261)	✓
DHCP Static @IP	✓
SIP account	1
Web interface configuration	✓
Sécurité password	✓
Audio (G.711, G.726, GSM)	✓
Audio settings : microphone, speaker, echo cancellation	✓
PC pop-up video software	✓
Video – IP video camera resolution	640 x 480 px
Video streaming : HTTP JPG, HTTP MJPEG, H.263	✓
Door phone (door latch activation)	2 gâches
Backlighted buttons	✓
Chain dialling or time slots choice	✓
Mechanical features	
Flush or surface mounted	✓
IP 65 Protection/Vandal resistant	✓/✓
Dimensions (mm) Flush mount	200x126x43
Dimensions (mm) Surface mount	205x130x43 ⁽¹⁾
Red colour (optional)	✓
Max current draw (mW)	3600

Video

- IP Camera definition : 640 x 480 Px
- HTTP JPG, HTTP MPG, H.263 video streaming
T50 Video phone compatibility
- Video settings : brightness, contrast and night vision

