



DEPAEPE
TELECOM

SecurAccess PMR

Handsfree doorphone (video optional)
Disabled compliant features



Main features

- Automatic call of pre-stored numbers when pressing memory buttons
- User friendly guidance with enlightened icons and digital voice announcement (complying with disabled help recommendations)
- Optional wide angle colour camera allowing visitors monitoring (complying with disabled help recommendations)
- Hearing aid induction coil (complying with disabled help recommendations)
- Selection of manual or automatic switching to off-hook or on-hook
- Local (using front panel keypad) or remote activation of a door latch (DTMF code)
- Exit button control
- Chain dialling (up to 5 numbers for each memory button) up to 9 times
- Local or remote programming
- Auxiliary dry contact
- Heating resistor
- Speaker boost feature (+10dB)



SecurAccess PMR

Handsfree doorphone (video optional)
Disabled compliant features



Description

- Aluminium vandal resistant housing (IK09 rating)
- Tamper resistant proof screws, grid protection for the speaker
- IP65 weather protection
- Flush or surface mount
- EEPROM memory backup
- Backlighted buttons, keypad and label display
- Keypad with Braille dots
- Models without keypad from 1 up to 8 buttons, models with keypad from 1 up to 4 buttons
- Compact models (small size) , 1 or 2 buttons
- Power supply included

Optional

- Built-in colour camera, wide angle (110°), with night vision, analog or IP
- PC programming device, to configure and duplicate the doorphone configuration
- Long range hearing aid induction coil (80cm)

SecurAccess PMR - 36 models

- SecurAccess PMR without keypad, analog or IP camera optional - 18 models
- SecurAccess PMR with keypad, analog or IP camera optional - 12 models
- SecurAccess Compact PMR without keypad, analog or IP camera optional - 6 models

Description	SecurAccess PMR without keypad	SecurAccess PMR with keypad	SecurAccess Compact PMR
Dialling buttons	1, 2, 3, 4, 6 or 8	1, 2, 3 or 4	1 or 2
Dimensions (HxLxP mm)	295 x 125 x 51	295 x 125 x 51	205 x 130 x 43
Dimensions (HxLxP mm) flush mount cut	235 x 104 x 57	235 x 104 x 57	168 x 115 x 48
Colour video camera (optional)	Analog or IP	Analog or IP	Analog or IP
Colour	Alu (red optional)	Alu (red optional)	Alu (red optional)



HENRI DEPAEPE S.A.S.

75/77 rue du Pré Brochet | 95110 SANNOIS - France
Tél.: +33 (0) 1 30 25 81 60 | Fax: +33 (0) 1 39 98 61 24

www.depaepe.com | © Copyright HENRI DEPAEPE SAS 2019. Reproduction interdite. Photos non contractuelles.

DEPAEPE Télécommunications se réserve le droit de modifier sans préavis les caractéristiques de ses produits en vue d'y apporter des améliorations techniques ou de respecter de nouvelles réglementations, nationales ou internationales

