

AMPLIDECT295™

Amplified Cordless Telephone with Integral Answering Machine



Twin version

available

AMPLIDECT295-2

CALLING/TALKING

- HAC
- Adjustable receiving volume : up to 30dB
- Speaker phone
- Adjustable speaker volume
- Phonebook up to 50 numbers
- Redial function for last 10 outgoing calls
- P/T dialing mode
- → R button for call waiting
- Hotkey to phonebook
- Hotkey to menu
- Flash function (100ms/300ms/600ms)
- Large keys

HANDSET LCD DISPLAY

- White backlight
- Choice of 7 languages (English, German, French, Italian, Dutch, Spanish and Russian)
- Dimensions : 40x40mm
- Display : Alphanumeric / 4 lines / Characters size : 7mm
- Clock
- Alarm
- Key lock
- Message waiting icon
- Communication time indication

CALLER ID *

- Name presentation in hook mode (type 1) and conversation mode (type 2)
 - 20 incoming numbers
 - o 10 outgoing numbers
- Caller ID also for Call waiting
- Possibility to transfer a call received to the directory
- Indicator call waiting
- Indicator new call

ANSWERING MACHINE

- 15 minutes of recording time
- 2 announcements
- → 2 answering machine modes (simple answering machine and answering machine recorder)
- Visual info. on the base about number of messages
- 4-digit user selectable remote codes
- Remote control for messages on handset
- Erase each/all messages
- → Audible time & date stamp on recorded messages
- 3 languages (English, German and French)

RINGER

geemarc

-

DELE

00

2

æ

2ABC 3 DE

5. 6

800

0

 $(\mathcal{Q}) \mathbf{R}$

- ➔ 5 polyphonic ringtones and 5 normal
- Adjustable ring volume (Mute + 5 positions)
- Customizable ringtones for phonebook contacts
- Shaker function

MULTI HANDSET

- Handset locator
- ➔ 3-way conference with privacy protection
- Up to 4 bases and up to 5 handsets
- Call transfer of external calls (when using several handsets)
- Intercom between handset

TECHNICAL SPECIFICATIONS

- ➔ 1 battery ni-Mh 2.4V 500mA (included)
- ➔ Memory storage
- ➔ Power supply by AC adapter (supplied)
- Dial/Decimal voice frequency
- Standby time : 4 days
- Continuous talk time : 8 hours
- GAP compliant
- Outdoor range 300 meters
- Indoor Range 50 meters
- Dimensions :
 - Handset :172x55x25 mm
 - o Base : 136x91x105 mm

OPTIONAL EXTRA

- AmpliDect295 AD
- PhotoDect295





LAMPLIDECT295UKV2

