

Audible and Visual Alarm D7



Application

Widely used in oil exploration, refining, chemical, military, and other hazardous environments and offshore oil platforms, oil tankers and other places for general lighting and task lighting purposes;

Suitable for energy-saving projects and repair and replacement places;

Suitable for higher protection requirements, moist places;

Suitable for explosive gas atmospheres of Zone 1, Zone 2 locations;

Applicable II A, II B, II Class C explosive gas atmospheres;

Suitable for temperature class T1-T6 group

Features

Aluminum die-cast shell, surface electrostatic spray.

Glass shade, with a strong impact resistance.

High corrosion resistance of stainless steel exposed fasteners;

LED light source, high brightness, long service life.

Pipe or cable wiring.

Technical Specification

Model: Beacon-7

Ex-mark: Exd[ib]ib II CT6/DIP A20 TA, T6

Rated voltage: AC220V 50Hz (if any special requirements please specify)

Protection class: IP66

Corrosion grade: WF1 * WF2

Flash Views: 150 times / min

Sound intensity: $\geq 120\text{dB}$

Intakes specifications: G3 / 4 ", suitable for $\Phi 10\text{mm} \sim \Phi 14\text{mm}$ cable

Terminals: $\leq 2.5\text{mm}^2$

Installation: pedestal (z),

Product Weight: 2.56kg

Dimension (mm)

