



## MKS-26/WS

Order No.: 0132380

Price upon request

### PRODUCTINFOS

#### Pair of miniature speaker systems, 8 Ω, 10 W

- For general applications, very small dimensions
- 6.5 cm (2.5") full range speaker
- Good sound characteristics and speech intelligibility
- Black (SW) or white (WS) plastic cabinet
- Mounting bracket with ball joint for turning, pivoting and tilting
- For completing the low-frequency sound reproduction, an additional subwoofer system is recommended (e.g. SOUND-100SUB)

### TECHNICAL SPECIFICATIONS

#### MKS-26/WS

Active/passive	passive
Total power rating	20 W
Power rating (RMS)	10 W

**MKS-26/WS**

Impedance	8 $\Omega$
Frequency range	150-22,000 Hz
Midrange speaker	6.5 cm (2.5") full range speaker
Number of speakers	1
Speaker size	6.5 cm (2")
Sensitivity	88 dB/W/m
Max. rated SPL	100 dB
Housing material	plastic
Colour	white
Mounting device	Mounting plate with ball joint
Admiss. ambient temp.	0-40 °C
Dimensions	90 x 90 x 115 mm
Width	90 mm
Height	90 mm
Depth	115 mm
Weight	0.45 kg
Inputs	spring-load. speaker term.