




<b>Product Name</b>	<b>ezOutlet2</b>			
<b>Brief Description</b>	ezOutlet2 is designed to automatically check if the network connection is online. Should the network goes off-line the outlet is designed to automatically power-cycle. Useful as a watchdog to ensure remote network (router/modem) is 24/7 online. Features: remotely turn outlet On / Off / Reset via free Android / iOS APP; secure outlet to reset only to avoid accidental turn offs and set schedules.			
<b>Package contents</b>	<ol style="list-style-type: none"> <li>1) Device</li> <li>2) Quick Installation Guide</li> <li>3) LAN cable</li> <li>4) IEC power cable</li> <li>5) Wall Mounting Template</li> </ol>			
<b>Model No.:</b>	<b>EZ-22b</b>	<b>EZ-32f</b>	<b>EZ-32g</b>	
<b>Image:</b>				Sockets by request. example: French ~ Type E Australian ~ Type I Swiss ~ Type J Danish ~ Type K
<b>Socket type</b>	NEMA (Type B)	Schuko shuttered (Type F, CEE 7/4, 7/17)	UK shuttered (Type G, BS1363, MS589, SS145)	
<b>Certification</b>	FCC	CE, LVD, RoHS Compliant		
<b>Electrical Rating</b>	Input: 100~240V, 50/60Hz. Output: 10A			
<b>Breaker</b>	10A (Thermal fuse)			
<b>Control and management interface;</b>	<ol style="list-style-type: none"> <li>1. Cloud4UIS.com</li> <li>2. ezDevice APP (available free on iOS APP store or Google Play)</li> <li>3. LAN Web user interface</li> <li>4. API</li> </ol>			
<b>Network Access</b>	10 / 100 Base-T, RJ45 (Cat. 5)			
<b>LED Indicator</b>	Green (Internet & Auto Reboot status), Red (Outlet status), Yellow (Server status) LED			
<b>Function Button</b>	<ol style="list-style-type: none"> <li>1) Press 1x to toggle [Auto Reset] or [Manual Control] function</li> <li>2) Press 2x to toggle (within 1 second) to toggle Outlet Power On or Off</li> <li>3) Press and Hold 10seconds to "Reset to Factory Default"</li> </ol>			
<b>Support</b>	Android, iOS APP / Internet Explorer / Chrome / Java / Safari browser			
<b>Network Protocols</b>	HTTP, TCP/IP, UDP, Dynamic DNS, DNS Client, DHCP, API.			
<b>Operating Environment</b>	0°C ~ 60°C at 10% ~ 90% relative humidity. <i>For indoor use only.</i>			
<b>Package option</b>	White Box / Bulk			
<b>Package dimension</b>	180 x 150 x 60 mm			
<b>Net(Gross) weight / set</b>	0.37kgw(0.47kgw)	0.42kgw(0.52kgw)	0.42kgw(0.52kgw)	TBD
<b>Carton measurement</b>	790 x 390 x 340 mm (50 sets per standard carton)			

Mega System Technologies, Inc. reserves the right to change the specifications herein without prior notice  
 Please re-confirm the specifications at time of inquiry