

# SECURPHONE SIP



**Weatherproof and vandal resistant SIP security telephones.**



## IP 65 Weatherproof protection

- Superior resistance to dust and water
- Perfect for inside or outside installation



## Vandal resistant (IK9 rated)

- 4 mm thick aluminium housing, tamper resistant proof screws, armed handset cord which cannot be dismantled

## Efficient

- Flush or surface mount
- Keypad with Braille dots
- Keypad, buttons and label display can be continuously back-lighted and (or) when going off-hook and (or) when ringing
- Flashing leds can be activated when going off-hook and (or) when ringing
- Adjustable amplified speaker
- 2 auxiliary dry contacts to activate cameras, lights, etc. when going off-hook and (or) when ringing
- Adjustable ringer volume (6 steps) up to 100 dB
- Hearing aid compatible
- EEPROM memory backup

## SIP

- 1 SIP account
- PoE powered or with external power supply (included)
- Auto-provisionning, automatic firmware update
- Web interface configuration DHCP-PPPOE-@Static IP
- Second failover Sip server
- Network address translation (NAT)
- Get @IP by voice menu
- Audio codecs : G.711, G.723, G.726, G.729
- QoS, VAD, CNG, LEC – Packet Loss Compensation
- SNTP – Administrator/User password



# SECURPHONE SIP

## SECURPHONE SIP – 5 MODELS

- No keypad/Hot line call (automatic dialling of one programmed number) when picking up the handset
- No keypad, 2 or 4 memory buttons
- Keypad
- Keypad and 4 memory buttons

Description	No keypad models	Models with keypad
Number of buttons	0-2 or 4	0 or 4
PoE or with power supply (included)	✓	✓
Keypad, buttons and label display backlight activation	✓	✓
Flashing leds activation (off-hook, ringing)	✓	✓
Keypad with Braille dots		✓
Eeprom memory backup	✓	✓
Hearing aid compatible	✓	✓



Technical specifications	No keypad models	Models with keypad
Flush or surface mount	✓	✓
Vandal resistant with IK9 rating	✓	✓
IP 65 Weather resistance	✓	✓
Natural ventilation	✓	✓
2 auxiliary dry contacts	✓	✓
Amplified speaker	✓	✓
Adjustable ringer volume (6 steps) up to 100 dB	✓	✓
Dimensions (mm) Flush mount	290 x 120 x 56	290 x 120 x 56
Dimensions (mm) Surface mount	294 x 125 x 59	294 x 125 x 59
Red color (optional)	✓	✓



**Depaepe**  
Telecom

S.A.S. HENRI DEPAEPE  
75-77, rue du Pré-Brochet – BP 80107  
95112 SANNOIS CEDEX – France  
Tel. : +33 (0)1 30 25 81 60  
Fax : +33 (0)1 39 98 61 24  
[www.depaep.com](http://www.depaep.com)

