

Zorgtoestel voor senioren R15P

De R15P brengt prijs/kwaliteit verhouding toegankelijk voor de zorgsector. Het intuïtieve interface van de R15P, maakt het zeer eenvoudig om in gebruik te nemen en is er minimale uitleg nodig.

- Eenvoudig in gebruik
- HD Geluidskwaliteit, met extra luide instelbare speakers
- Boost knop, aanpasbare beltonen
- Hearing Aid Compatible (HAC)
- Grote toetsen, SOS-knop
- Luide beltonen, Flitslicht
- Ondersteund PoE
- Compatible op o.a. Asterisk, BroadSoft



Toestel eigenschappen

- 1 Line (Support 1 SIP account)
- Support Call Waiting, Call Forward, Call Transfer
- Call on Hold, Mute, Auto-answer, Redial, DND
- Local 3-Way Conference
- Volume Adjustable, Ring tones Selectable
- Speed Dial, Hotline
- Network Packet Capture
- Country Ringtone Signal
- Direct IP call
- Auto Redial, Call Return
- Dial Plan
- XML Browser
- Hot Desking
- Keypad Lock
- Action URL/URI
- Phonebook (500 groups), Blacklist (100 groups), Call logs (100 entries)
- 5 Remote Phone Book URL Supported
- LDAP
- Multi-Languages Support

IP-PBX eigenschappen

- SMS, MWI
- Music on hold, Intercom
- Call Pickup, Group Call Pickup
- Call Recording
- Anonymous Call, Anonymous Call Rejection

Audio eigenschappen

- HD Voice with high volume
- Hearing Aid Compatible (HAC)
- Wideband Codec: G.722
- Narrowband Codec: PCMA, PCMU, G.729, G.723_53, G.723_63, G.726_16, G.726_24, G.726_32, G.726_40
- VAD, CNG, Echo Canceller
- Full-Duplex Speakerphone

Security eigenschappen

- Support HTTPS (SSL)
- Support SRTP for Voice Data Encryption
- Support Login for Administration
- SIP Over TLS

Netwerk eigenschappen

- SIP V1(RFC2543), V2(RFC3261)
- Static IP/DHCP for IP configuration
- 3 DTMF modes: In-Band, RFC2833, SIP INFO
- HTTP/HTTPS Web Server for Management
- NTP for Auto Time Setting
- TFTP/FTP/HTTP/HTTPS Protocols
- 802.1Q VLAN

Administratie eigenschappen

- Auto provisioning using FTP/TFTP/HTTP/HTTPS/PnP
- Dial through IP PBX Using Phone Number
- Dial through IP PBX Using URL Address
- Configuration Managements with web, keypad on the phone, and Auto Provisioning
- SNMP
- TR069

Fysieke eigenschappen

- Audiocodes Chipset
- 2.9" 132x64 Graphical LCD with Backlight
- 25 Keys (with 1 SOS key, 4 Soft Keys, 3 Image Programmable Keys)
- 3 LED Lights (1 Power Light, 1 Handfree Light and 1 SOS Light)
- Up to 10 Wireless Emergency Pendants Supported (Optional)
- RJ9 Handset Jack and Headset Jack
- 2 RJ45 10/100 Ethernet Jacks
- AC Power Adapter: Input: AC 100-240V; Output: DC 5V/1A
- PoE: IEEE 802.3af
- Giftbox Size: 202*239.5*102.5 (mm), weight: 1.19 kg