



746 WALL TELEPHONE SIP

The GPO 746 Wallphone is easily fixed to the wall and is the ideal addition to any home or business. There's even an extra-long handset curly cord so you can circle the room while you talk.

FEATURES:

- Jacks: 10/100 RJ45 WAN, RJ9 Handset
- Dimensions: W 14.5cm x D 8.5cm x H 24.0cm
- Weight: 750g
- Easy: GUI
- Administration: Web Based speed-dial key setting for m1-m6
- Firmware Upgrade via Web
- Auto Provisioning
- IP Address auto announcement from Handset
- Codec: G.711a/u-low/G.723/G.729
- Network Protocol: Telnet / http Server / DNS Client
- PPPoE / Static / DHCP Client IP assignment.
- ToS field / VLAN IEEE 802.1 p/q
- SIP: SIP V1 (RFC2543) SIP V2 (RFC3261)
- Security: Web Login authentication for web setup
- MD5 for SIP authentication (RFC2069/ RFC2617)
- Voice Quality: CNG Comfortable Noise Generator
- LEC Line Echo Canceller: Jitter Buffer
- VAD Voice Activity Detection: Packet Loss Compression
- EMI USA: FCC Part 15B,D ICES-003 EU: EN 55022
- EMC EU: EN 55024, EN 61000-4-4, EN 61000-3-2, IEC 61000-4-5
- EN 61000-3-3, IEC 61000-4-6, EN 61000-4-2, IEC 61000-4-11
- RoHS: Comply with directive 2002/95/ EC RoHS (2005/613/EC)
- Temperature Storage Operating: -10C to +60C 0C to +40C.