# Panasonic ideas for life

### **KX-TS880**

- New business-use ITS
- 10 One Touch Speed Dial Key
- Caller ID and Speaker Phone

Top Business Success Begins





## Strong Support for All Types of Business

The Integrated Telephone System combines function and design to meet a wide range of business situations. All required functions are designed based on special business specifications and ensure extremely easy operation.

#### Outstanding Features with Built-In Quality

#### New businessuse ITS

New 10 Specific Speci

In order to reliably support everyday business activities, the KX-TS880 features a wide range of indispensable functions, a comfortable handset, convenient 3-line LCD, Caller ID and 2-Step Tilt Angle.

#### 10 One Touch Speed Dial Key

10 one-touch speed dial numbers are ideal for storing emergency or frequently dialed numbers. You can also store and retrieve 20 phone numbers for two-touch speed dialing. A total of 30 speed dial numbers will save you searching and dialing time.

#### Caller ID\* and Speaker Phone



KX-TS880 is suitable for Caller ID service. The 3-Line LCD displays caller's information. You can know who's calling before you answer.

\* Requires subscription to Caller ID service by a telephone company.

#### 2-Step Tilt Angle

The 2-Step Tilt Angle allows easy adjustment when the telephone is placed on a desk. Careful engineering and design ensure easy use while minimizing user inconvenience.



#### Wall Mountable

There's no need to worry if you can't find a suitable place to put your KX-TS880. You can mount it right on the wall for functional use.



#### Other Features

- Programmable Flash Time setting
- Long Handset Cord (39cm)
- Dial Lock (4digits PIN)
- Auto Redial

- Electronic Hold
- Ringer Indication (LED)
- Mute

- Clock
- Speakerphone
- Headset Jack

#### **Specifications**

Call Restriction	•	Volume	Electrical (4 steps)
One Touch Dial (Stations)	10stations	SP Volume	Electrical (8 steps)
Redial	• (20stations)	Phonebook	50stations (Number & Name)
One-Touch Tone Switching	•	LCD	3Line (Dot & 7segment & Pict)
Tone/Pulse Setting	Programmable	Wall Mountable	•
Timed Flash	600ms	Caller ID Memory	50 stations
Insertable Pause	● (3.5sec)	Dimensions (W x D x H)	172 mm x 220 mm x 93mm
Ringer Selector (step)	SW (Off / Low / High)	Weight	550 g

